



Safety Data Sheet

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • **BC-622A Part A**
Synonyms • Polyester polyol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Reflective Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer • Luxium Solutions
 17900 Great Lakes Parkway
 Hiram, OH 44234
 United States
 www.luxiumsolutions.com

Telephone (General) • 4 4 0 -834-5600

1.4 Emergency telephone number

Contract # 6493674

U.S. & Canada • 1-800-255-3924 – VelocityEHS

International • +1-813-248-0585 – VelocityEHS

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 2015/830]

According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP • Flammable Liquids 3 - H226
 Germ Cell Mutagenicity 1B - H340

DSD/DPD • Carcinogenic Substances - Category 2
 Mutagenic Substances - Category 2
 R10, R45, R46

2.2 Label Elements

CLP

DANGER



- Hazard statements** • H226 - Flammable liquid and vapour
 H340 - May cause genetic defects.
 H350 - May cause cancer.

Precautionary statements

- Prevention** • P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground and/or bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P280 - Wear protective gloves and eye/face protection , .
 P281 - Use personal protective equipment as required.

- Response** • P370+P378 - In case of fire: Use appropriate media for extinction.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.

- Storage/Disposal** • P403+P235 - Store in a well-ventilated place. Keep cool.
 P405 - Store locked up.
 P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD



- Risk phrases** • R10 - Flammable.
 R45 - May cause cancer.
 R46 - May cause heritable genetic damage.

- Safety phrases** • S53 - Avoid exposure - obtain special instructions before use.

2.3 Other Hazards

- CLP** • According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

- DSD/DPD** • According to European Directive 1999/45/EC this material is considered dangerous.

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

- OSHA HCS 2012**
- Flammable Liquids 3
 - Eye Irritation 2
 - Carcinogenicity 2
 - Reproductive Toxicity 2
 - Specific Target Organ Toxicity Repeated Exposure 2

2.2 Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- Flammable liquid and vapour
 - Causes serious eye irritation
 - Suspected of causing cancer.
 - Suspected of damaging fertility or the unborn child.
 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- Prevention**
- Obtain special instructions before use.
 - Do not handle until all safety precautions have been read and understood.
 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - Keep container tightly closed.
 - Ground and/or bond container and receiving equipment.
 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - Use only non-sparking tools.
 - Take precautionary measures against static discharge.
 - Do not breathe mist/vapours/spray.
 - Wash thoroughly after handling.
 - Wear protective gloves, clothing, and eye/face protection, .
- Response**
- In case of fire: Use appropriate media for extinction.
 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - If eye irritation persists: Get medical advice/attention.
 - IF exposed or concerned: Get medical advice/attention.
- Storage/Disposal**
- Store in a well-ventilated place. Keep cool.
 - Store locked up.
 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.2 Label elements

WHMIS



WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2A
- Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a substance.

3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
1-Methoxy-2-propanol acetate	CAS: 108-65-6 EC Number: 203-603-9 EU Index: 607-195-00-7	50% TO 60%	Ingestion/Oral-Rat <u>LD50 • 8532 mg/kg</u> Skin-Rabbit LD50 • >5 g/kg	EU DSD/DPD: Annex VI, Table 3.2: R10 EU CLP: Annex VI, Table 3.1: Flam. Liq. 3, H226 OSHA HCS 2012: Not Classified	NDA
Non-Hazardous material Non-Regulated	NDA	30% TO 40%	NDA	EU DSD/DPD: Not Classified EU CLP: Not Classified OSHA HCS 2012: Not Classified	NDA
Xylene	CAS: 1330-20-7 EC Number: 215-535-7 EU Index: 601-022-00-9	1% TO 5%	Ingestion/Oral-Rat <u>LD50 • 4300 mg/kg</u> Inhalation-Rat <u>LC50 • 5000 ppm 4 Hour(s)</u> Skin-Rabbit LD50 • >1700 mg/kg	EU DSD/DPD: Annex VI, Table 3.2: R10; Xn; R20/21; Xi; R38 EU CLP: Annex VI, Table 3.1: Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (inhl); Skin Irrit. 2; Eye Irrit. 2; Repr. 1B (Inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.	NDA
Solvent naphtha (petroleum), light aromatic	CAS: 64742-95-6 EC Number: 265-199-0 EU Index: 649-356-00-4	1% TO 5%	Ingestion/Oral-Rat <u>LD50 • 8400 mg/kg</u>	EU DSD/DPD: Annex VI, Table 3.2: Carc. Cat. 2; R45; Muta. Cat. 2; R46; Xn; R65 EU CLP: Annex VI, Table 3.1: Carc. 1B, H350; Muta. 1B, H340; Asp. Tox. 1, H304 OSHA HCS 2012: Eye Irrit. 2	NDA
Ethylbenzene	CAS: 100-41-4 EC Number: 202-849-4 EU Index: 601-023-00-4	1% TO 5%	Ingestion/Oral-Rat <u>LD50 • 3500 mg/kg</u> Inhalation-Rat <u>LC50 • 55000 mg/m³ 2 Hour(s)</u> Skin-Rabbit LD50 • >5000 mg/kg	EU DSD/DPD: Annex VI, Table 3.2: F; R11; Xn; R20-48/20-65 EU CLP: Annex VI, Table 3.1: Flam. Liq. 2, H225; Acute Tox. 4, H332; STOT RE 2, H373 (Hearing Organs, Inhl); Asp. Tox. 1, H304 OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (inhl); Eye Irrit. 2; Carc. 2 (inhl); Repr. 2 (inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit. (inhl); STOT RE 2 (Ear, Inhl); Asp. Tox. 1	NDA

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

- Wash skin with soap and water. Take off contaminated clothing and wash before reuse. If irritation develops and persists, get medical attention.

Eye

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

- Do NOT induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness, is unconscious or convulsing. Have victim drink 60 to 240 ml (2 to 8 oz.) of water. If vomiting occurs naturally, have victim rinse mouth with water again. Get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media • Use dry chemical, foam or fog.

Unsuitable Extinguishing Media • No data available

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- Containers may explode when heated. Vapor explosion hazard indoors, outdoors or in sewers. HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Many liquids are lighter than water. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Runoff to sewer may create fire or explosion hazard. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

- Oxides of carbon, Carbon dioxide, and Carbon monoxide.

5.3 Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing mist, vapors, and/or spray. Avoid contact with skin, eyes or clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

6.2 Environmental precautions

- Avoid run off to waterways and sewers.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors. All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal. LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Use only in well ventilated areas. Avoid contact with heat and ignition sources. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe mist, vapors, or spray. Avoid contact with skin, eyes or clothing. Use only non-sparking tools. Take precautionary measures against static charges. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool/low-temperature, well-ventilated place. Keep away from heat and ignition sources. Keep container closed when not in use. Keep away from incompatible materials.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines				
	Result	ACGIH	NIOSH	OSHA
Ethylbenzene (100-41-4)	TWAs	20 ppm TWA	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA
	STELs	Not established	125 ppm STEL; 545 mg/m3 STEL	Not established
Xylene (1330-20-7)	TWAs	100 ppm TWA	Not established	100 ppm TWA; 435 mg/m3 TWA
	STELs	150 ppm STEL	Not established	Not established

8.2 Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical, ventilating and/or lighting equipment.

Personal Protective Equipment

Respiratory

- Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear safety goggles.

Skin/Body

- Wear appropriate gloves.

Environmental Exposure Controls

- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow

best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

LLV = Limit Level Value is the exposure limit for 8-hour work day

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

STV = Short-term exposure limit based on 15-minute exposure

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

VLA-EC = Valor Límite Ambiental Exposición de Corta Duración is the short-term exposure limit based on 15-minute exposure

VLA-ED = Valor Límite Ambiental Exposición Diaria is the limit for the daily average concentration

Section 9 - Physical and Chemical Properties

9.1 Information on Basic Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Thick, white liquid with a sweet, hydrocarbon odor.
Color	White	Odor	Sweet, hydrocarbon odor.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	136 to 140 °C(276.8 to 284 °F)	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	= 1.02 Water=1	Water Solubility	Data lacking
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking		
Flammability			
Flash Point	27 °C(80.6 °F)	UEL	7 %
LEL	0.9 %	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Avoid heat, sparks, open flames and other ignition sources. Incompatible materials.

10.5 Incompatible materials

- Oxidizing agents.

10.6 Hazardous decomposition products

- Carbon dioxide and carbon monoxide.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Components		
1-Methoxy-2-propanol acetate (50% TO 60%)	108-65-6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 8532 mg/kg; Skin-Rabbit LD50 • >5 g/kg
Xylene (1% TO 5%)	1330-20-7	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4300 mg/kg; Liver:Other changes; Kidney, Ureter, and Bladder:Other changes; Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Inhalation-Man LCLo • 10000 ppm 6 Hour(s); Behavioral:General anesthetic; Lungs, Thorax, or Respiration:Cyanosis; Blood:Other changes; Inhalation-Human TCLo • 200 ppm; Sense Organs and Special Senses:Olfaction:Other changes; Sense Organs and Special Senses:Eye:Conjunctive irritation; Lungs, Thorax, or Respiration:Other changes; Skin-Rabbit LD50 • >1700 mg/kg; Irritation: Eye-Rabbit • 5 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Reproductive: Inhalation-Rabbit TCLo • 1 g/m ³ 24 Hour(s)(7-20D preg); Reproductive Effects:Effects on Fertility:Abortion; Inhalation-Rat TCLo • 50 mg/m ³ 6 Hour(s)(1-21D preg); Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Craniofacial (including nose and tongue); Inhalation-Rat TDLo • 200 ppm 6 Hour(s)(4-20D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Effects on Newborn:Behavioral
Solvent naphtha (petroleum), light aromatic (1% TO 5%)	64742-95-6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 8400 mg/kg; Behavioral:Somnolence (general depressed activity); Behavioral:Tremor; Lungs, Thorax, or Respiration:Other changes; Irritation: Eye-Rabbit • 100 µL 24 Hour(s) • Mild irritation; Reproductive: Inhalation-Rat TCLo • 1500 ppm (9W male/9W pre-16D post); Reproductive Effects:Effects on Newborn:Growth statistics (e.g., reduced weight gain)
Ethylbenzene (1% TO 5%)	100-41-4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 3500 mg/kg; Inhalation-Rat LC50 • 55000 mg/m ³ 2 Hour(s); Inhalation-Guinea Pig LCLo • 2500 ppm 8 Hour(s); Behavioral:Coma; Skin-Rabbit LD50 • 17800 µL/kg; Irritation: Eye-Rabbit • 500 mg • Severe irritation; Skin-Rabbit • 15 mg 24 Hour(s)-Open • Mild irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 550 ppm 8 Hour(s) 5 Day(s)-Intermittent; Sense Organs and Special Senses:Ear:Change in acuity; Sense Organs and Special Senses:Ear:Changes in cochlear structure or function; Inhalation-Rat TDLo • 200 ppm 13 Week(s)-Intermittent; Sense Organs and Special Senses:Ear:Changes in cochlear structure or function; Mutagen: Specific locus test • Intraperitoneal-Mouse • 754 µmol/L; Micronucleus test • Unreported Route-Hamster • Embryo (Somatic cell) • 25 mg/L; Sister chromatid exchange • Unreported Route-Human • Lymphocyte (Somatic cell) • 10 mmol/L; Mutation in Mammalian Somatic Cells • Unreported Route-Mouse • Lymphocyte (Somatic cell) • 80 mg/L; Reproductive: Inhalation-Rabbit TCLo • 1 g/m ³ 24 Hour(s)(7-20D preg); Reproductive Effects:Effects on Fertility:Abortion; Inhalation-Rat TCLo • 1000 ppm (6-20D preg); Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Inhalation-Rat TCLo • 96 ppm 7 Hour(s)(1-19D preg); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Inhalation-Rat TCLo • 600 mg/m ³ 24 Hour(s)(7-15D preg); Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetal death; Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Tumorigen / Carcinogen: Inhalation-Mouse TCLo • 750 ppm 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Bronchiogenic carcinoma; Liver:Tumors; Inhalation-Rat TCLo • 23400 mg/kg 104 Week(s)-Intermittent; Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Kidney, Ureter, and Bladder:Kidney tumors; Reproductive Effects:Tumorigenic Effects:Testicular tumors; Inhalation-Rat TCLo • 750 ppm 6 Hour(s) 2 Year(s)-Intermittent;

Tumorigenic: Carcinogenic by RTECS criteria; Kidney, Ureter, and Bladder: Tumors

GHS Properties	Classification
Acute toxicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Serious eye damage/Irritation	EU/CLP • Data lacking OSHA HCS 2012 • Eye Irritation 2
Skin sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Respiratory sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Aspiration Hazard	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Carcinogenicity	EU/CLP • Carcinogenicity 1B; May cause cancer OSHA HCS 2012 • Carcinogenicity 2
Germ Cell Mutagenicity	EU/CLP • Germ Cell Mutagenicity 1B OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	EU/CLP • Data lacking OSHA HCS 2012 • Toxic to Reproduction 2
STOT-SE	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
STOT-RE	EU/CLP • Data lacking OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2

Potential Health Effects

Inhalation

Acute (Immediate)

- Vapors may cause irritation to the respiratory system.

Chronic (Delayed)

- Exposure to relatively low concentrations of ethylbenzene for several days to weeks resulted in potentially irreversible damage to the inner ear and hearing of animals.

Skin

Acute (Immediate)

- May cause irritation.

Chronic (Delayed)

- No data available

Eye

Acute (Immediate)

- Causes serious eye irritation.

Chronic (Delayed)

- No data available

Ingestion

Acute (Immediate)

- Effects unknown.

Chronic (Delayed)

- No data available

Mutagenic Effects

- May cause genetic defects.

Carcinogenic Effects

- May cause cancer.

Carcinogenic Effects		
	CAS	IARC
Ethylbenzene	100-41-4	Group 2B-Possible Carcinogen

Reproductive Effects

- Suspected of damaging fertility or the unborn child.

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information**12.1 Toxicity**

- Material data lacking.

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations**13.1 Waste treatment methods****Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1263	Paint	3	III	NDA
TDG	UN1263	PAINT	3	III	NDA
IMO/IMDG	UN1263	PAINT	3	III	NDA
IATA/ICAO	UN1263	Paint	3	III	NDA

14.6 Special precautions for user

- None specified.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

- Data lacking.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
1-Methoxy-2-propanol acetate	108-65-6	Yes	No	Yes	No	Yes
Ethylbenzene	100-41-4	Yes	No	Yes	No	Yes
Solvent naphtha (petroleum), light aromatic	64742-95-6	Yes	No	Yes	No	Yes
Xylene	1330-20-7	Yes	No	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Ethylbenzene	100-41-4	B2, D2A, D2B
• Xylene	1330-20-7	B2, D2A, D2B
• Solvent naphtha (petroleum), light aromatic	64742-95-6	B3, D2B
• 1-Methoxy-2-propanol acetate	108-65-6	B3

Canada - WHMIS - Ingredient Disclosure List

• Ethylbenzene	100-41-4	0.1 %
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

Environment

Canada - CEPA - Priority Substances List

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Priority Substance List 1 (substance not considered toxic)
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

Environment**U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• Ethylbenzene	100-41-4	(listed under Ethyl benzene)
• Xylene	1330-20-7	(isomers and mixtures)
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Ethylbenzene	100-41-4	1000 lb final RQ; 454 kg final RQ
• Xylene	1330-20-7	100 lb final RQ; 45.4 kg final RQ
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Ethylbenzene	100-41-4	0.1 % de minimis concentration
• Xylene	1330-20-7	1.0 % de minimis concentration
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

United States - California**Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Ethylbenzene	100-41-4	carcinogen, initial date 6/11/04
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Ethylbenzene	100-41-4	54 µg/day NSRL (inhalation); 41 µg/day NSRL (oral)
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

• Ethylbenzene	100-41-4	Not Listed
• Xylene	1330-20-7	Not Listed
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1-Methoxy-2-propanol acetate	108-65-6	Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

15.3 Other Information

- **WARNING:** This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information**Relevant Phrases (code & full text)**

- H225 - Highly flammable liquid and vapour
- H304 - May be fatal if swallowed and enters airways
- H312 - Harmful in contact with skin
- H315 - Causes skin irritation
- H332 - Harmful if inhaled
- H373 - May cause damage to organs through prolonged or repeated exposure.
- R11 - Highly flammable.
- R20 - Harmful by inhalation.
- R20/21 - Harmful by inhalation and in contact with skin.
- R38 - Irritating to skin.
- R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R65 - Harmful: may cause lung damage if swallowed.

Revision Date

- 16/May/2023

Preparation Date

- 05/March/2015

Disclaimer/Statement of Liability

- Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgement.

Key to abbreviations

NDA = No Data Available